



Vented Control Valve Features and Breakdown

Model	Features	Options	Burner Sizes
MA & MAHC-GC 	<ul style="list-style-type: none"> *Manual On/Off w/ Knob or Wrench Operations ONLY *Low Profile Design *Max Inlet 14" W.C. *Valve Temp Rating 300° *90,000 BTU's (NG/LP) - MA *240,000 BTU's (NG/LP) - MAHC 	N/A	MA 2 Burner/Glass/Kiva – 18"–42" (NG/LP) 3 Burner – 18"–30" (NG/LP) MAHC Jumbo/Jumbo Slimline 24"–84" (NG/LP)
SPQMKN & SPQMKL 	<ul style="list-style-type: none"> *Standing Pilot System *Manual On/Off Operations ONLY *Low Profile Design *Max Inlet 14" W.C. *Valve Temp Rating 300° *(NG) 90,000 BTU's *(LP) 90,000 BTU's 	N/A	2 Burner/Glass/Kiva – 18"–30" (NG) 18"–42" (LP) 3 Burner – 18"–24" (NG) 18"–36" (LP) Jumbo/Jumbo Slimline N/A (NG) N/A (LP)
HCSPK-N & HCSPK-LP 	<ul style="list-style-type: none"> *Standing Pilot System *Manual On/Off Operations ONLY *Max Inlet 14" W.C. *Valve Temp Rating 250° *(NG) 142,000 BTU's *(LP) 142,000 BTU's 	*GCRK (On/Off) remote	2 Burner/Glass/Kiva – 18"–42" (NG) 18"–60" (LP) 3 Burner – 18"–42" (NG) 18"–42" (LP) Jumbo/Jumbo Slimline 24"–30" (NG) 24"–48" (LP)
MVQMKN & MVQMKL 	<ul style="list-style-type: none"> *Standing Pilot System *On/Off Operations ONLY *Low Profile Design *Max Inlet 14" W.C. *Valve Temp Rating 175° *(NG) 3"–5" W.C. 70,000 BTU's *(LP) 8"–12" W.C. 110,000 BTU's 	*GCRK (On/Off) remote *(On/Off) Wall Switch not available from GC	2 Burner/Glass/Kiva – 18"–30" (NG) 18"–42" (LP) 3 Burner – 18"–24" (NG) 18"–36" (LP) Jumbo/Jumbo Slimline N/A (NG) 24"–30" (LP)

 <p>MMVKR-NG & MMVKR-LP</p>	<ul style="list-style-type: none"> *Standing Pilot System *Variable Flame Height *Low Profile Design *Max Inlet 14" W.C. *Valve Temp Rating 225° *(NG) 7" W.C. 120,000 BTU's *(LP) 7"-14" W.C. 120,000 BTU's 	<p>N/A</p>	<p>2 Burner/Glass/Kiva – 18"–42" (NG) 18"–42" (LP) 3 Burner – 18"–42" (NG) 18"–42" (LP)</p> <p>Jumbo/Jumbo Slimline 24" – 30" (NG) 24"-30" (LP)</p>
 <p>HCMVQMKN & HCMVQMKLP</p>	<ul style="list-style-type: none"> *Standing Pilot System *High Volume Output Millivolt System *On/Off Operations ONLY *Max Inlet 14" W.C. *Valve Temp Rating 175° *(NG) 3"-5" W.C. 370,000 BTU's *(LP) 8"-12" W.C. 560,000 BTU's 	<ul style="list-style-type: none"> *GCRK (On/Off) remote *(On/Off) Wall Switch not available from GC 	<p>2 Burner/Glass/Kiva – 18"–60" (NG) 18"–42" (LP) 3 Burner – 18"–42" (NG) 18"–42" (LP)</p> <p>Jumbo/Jumbo Slimline 24"-108" (NG) 24"-120" (LP)</p>
 <p>MVKEIKN & MVKEIKLP</p>	<ul style="list-style-type: none"> *Non-Standing Pilot *2-D Cell Battery Electronic Ignition *Pilot on Demand System *On/Off Operations ONLY *Max Inlet 14" W.C. *Valve Temp Rating 175° *(NG) 3"-7" W.C. 120,000 BTU's *(LP) 8"-14" W.C. 140,000 BTU's 	<ul style="list-style-type: none"> *GCRK (On/Off) remote 	<p>2 Burner/Glass/Kiva – 18"–42" (NG) 18"–42" (LP) 3 Burner – 18"–30" (NG) 18"–36" (LP)</p> <p>Jumbo/Jumbo Slimline N/A (NG) 24"-30" (LP)</p>
 <p>EIS & EIS-LP</p>	<ul style="list-style-type: none"> *Non-Standing Pilot *Pilot on Demand System *24V Electronic Ignition *On/Off Operations ONLY *In-Wall Design *6'-10' Pilot Assembly *Max Inlet 14" W.C. *Valve Temp Rating 175° *(NG) 3"-7" W.C. 200,000 BTU's *(LP) 8"-14" W.C. 320,000 BTU's 	<ul style="list-style-type: none"> *GCRK (On/Off) remote *(On/Off) Wall Switch not available from GC *WBPB12/24 	<p>2 Burner/Glass/Kiva – 18"–60" (NG) 18"–42" (LP) 3 Burner – 18"–42" (NG) 18"–42" (LP)</p> <p>Jumbo/Jumbo Slimline 24"-60" (NG) 24"-96" (LP)</p>
 <p>EIS-350 & EIS-350-LP</p>	<ul style="list-style-type: none"> *Non-Standing Pilot *Pilot on Demand System *24V Electronic Ignition *On/Off Operations ONLY *In-Wall Design *6'-10' Pilot Assembly *Max Inlet 14" W.C. *Valve Temp Rating 175° *(NG) 3"-7" W.C. 350,000 BTU's 	<ul style="list-style-type: none"> *GCRK (On/Off) remote *(On/Off) Wall Switch not available from GC *WBPB12/24 	<p>2 Burner/Glass/Kiva – 18"–60" (NG) 18"–42" (LP) 3 Burner – 18"–42" (NG) 18"–42" (LP)</p> <p>Jumbo/Jumbo Slimline 24"-120" (NG) 24"-120" (LP)</p>

	* (LP) 8" -14" W.C. 560,000 BTU's		
WBECs 	<ul style="list-style-type: none"> * Hot Surface Ignition System * Pilot on Demand System * LED Diagnostics * 12V Electronic Ignition * On/Off Operations ONLY * 24" Pilot Assembly * CSA Certified Control System * Max Inlet 14" W.C. * Valve Temp Rating 175° * 265,000 BTU (NG/LP) 	<ul style="list-style-type: none"> * GCRK-110 (On/Off) remote * WBPB12/24 	<ul style="list-style-type: none"> * All Fire-Pits * All Fire-tables * Outdoor Burners
Model	Features	Options	Application
GCRK 	<ul style="list-style-type: none"> * Basic On/Off Operations * RF Transmitter & Receiver * LCD Temp Display * Includes Batteries & Wall Plate 	N/A	<ul style="list-style-type: none"> * MVQMKN/LP * HCMVQMKN/LP * ALL EIS Configurations
WBPB-12/24 	<ul style="list-style-type: none"> * Bluetooth Wi-Fi & Manual Control * Connect with Home Automation OR Weather Smart App * 24V System 	N/A	<ul style="list-style-type: none"> * ALL EIS Configurations * WBECs